

## Vaetrix ETG Digital Pressure Gauge Comparison (0.1% Full Scale)

A quick look at the below comparison table will convince you of the overall value the Vaetrix ETG provides based on similar digital pressure gauges found in the industry. For a complete list of specifications, be sure to check our website at <u>vaetrix.com</u>.

Model 🛋	Vaetrix ETG	Crystal M1	Additel 680	Ashcroft 2089
Specification				
Accuracy	0.1% Full Scale	0.2% Reading	0.1% Full Scale	0.1% Full Scale
Display	Full Graphics	2 Line LCD	2 Line LCD	2 Line LCD
	Real Font (0.62")	(0.55")	(N/A)	(0.66")
	Green or Blue	Green Backlight	White Backlight	Green Backlight
	Backlight			
Ranges	9 Ranges	6 Ranges	14 Ranges	13 Ranges
	Vacuum to	30 to 10,000 PSI	Vacuum to 40,000	Vacuum to 7000
	30,000 PSI		PSI	PSI
Measurement	Gauge, Vacuum,	Gauge	Gauge, Vacuum,	Gauge, Vacuum,
Types	Compound		Compound	Compound
Communication	Micro-USB	None	Wireless	None
Standard	Batteries, NIST	Batteries, NIST	Batteries, NIST	Batteries, NIST
Accessories	Cert, Boot,	Cert, Boot, Manual	Cert, Boot, Manual	Cert, Manual
	Manual			
Battery Life	3 AA Alkaline	2 AA Alkaline	2 AA Alkaline	3 AAA Alkaline
	1500 Hours	900 Hours	1500 Hours	1000 Hours
Data Logging	<b>Yes</b> , (USB)	No	Yes - Wireless	No
	64,000 Points			
Alarms	Yes – Color	No	No	No
	Indication or Icon			
<b>Real Time Clock</b>	Yes	No	No	No
Snapshot	Yes	No	No	No
Feature				
Admin Control	Yes	No	No	No
Leak Test	Yes	No	Yes	No
Barometric	Yes	No	No	No
Sensor				
Pressure Port	¼" MNPT	¼" FNPT	¼" MNPT, ½"	¼" MNPT
		(Crystal Adapters)	MNPT, ¼" BSP,	
			M20 x 1.5,	
			Autoclave	
Wireless	Bluetooth	No	ISM 2.4 G	No
	(Optional -\$50)		(Optional - \$195)	



User Interface	6 Button	4 Button	4 Button	4 Button
	Real Font Menus	Menu/Symbols	Menu/Symbols	Menu/Symbols
Intrinsically Safe	Yes - Optional	No	No	Yes - Optional
Warranty	4 Year	2 Year	1 Year	1 Year
IP Rating	IP65	IP65	IP67	IP65
Enclosure	Zinc Alloy	Polycarbonate Blend	Polycarbonate	Stainless Steel
Operating	-10 to 50°C	-10 to 50°C	-10 to 50°C	-18 to 63°C
Temperature	14 to 122°F	14 to 122°F	14 to 122°F	0 to 150°F
Weight	23 oz	11.7 oz	18 oz	10 oz
Size	4" x 1.6" x 5.9"	4.1"x 1.7" x 4.8"	4" x 1.6" x 6.2"	3" Case
MSRP	\$693	\$974	\$840	\$1212
Image				

## Save Time Testing with Intuitive Menus and the free Hydro App



February 2023 Gauge Comparison – All Information herein believed accurate – Check Manufacturer's Website for Latest Information