

Vaetrix ETG series utilizes the latest digital technology to accurately solve pressure measurement applications. All MEMS pressure sensors are fully temperature compensated throughout the operating range. The easy to use interface and intuitive menu structure is the best in the industry. There are no encrypted symbols or abbreviations, just press the arrow keys to navigate the menu and select your choice. We take pride in manufacturing and designing products in the USA and have over thirty years of experience producing process instrumentation. Performance and reliability is backed by a four-year warranty.



- 0.05%, 0.1%, or 0.25% full scale accuracy over operating temperature
- Dual sensor technology to measure absolute and gauge pressure with one device
- High and low alarm settings with icon and red backlight indication
- Dedicated interface for leak test and min/max function
- Snapshot readings with date and time stamp
- Multi-session data logging capability (up to 64,000 records with date, time, and pressure)
- USB communications and Bluetooth option for Android mobile
- Tri-color graphics display with selectable backlight color for optimum viewing
- Twenty engineering units with the ability to select favorites

Includes: quick start guide, batteries, protective boot, NIST cert with data, and basic data-logging.




Panel Mount option available as 0.05% FS with USB power

Range Options (0.05%)	-15 to 15, -15 to 30 (Compound-Gas Only) 15, 30, 100, 300, 500, 1K, 3K, 5K, 10K (Isolated – Gas & Liquids)
Range Options (0.1% & 0.25%)	±5, 30, 100, 300, 500, 1K, 2K, 3K, 5K, 10K, 14.5K (Isolated – Gas & Liquids) All values referenced in PSI. Consult factory for additional range options.

Phone: 888-797-3740 / Email: sales@vaetrix.com / 143 Raymond Rd, Candia, NH 03034 USA

Parameter	Specifications (Consult Manual for Complete Details)	
Pressure Accuracy	±0.05%, ±0.1%, or ±0.25% of Full Scale <i>Includes all effects of temperature and stability based on one year</i>	
Vacuum Accuracy	±0.25% Full Scale <i>Applies to ranges 500 PSI and below with an isolated sensor</i>	
Barometric Accuracy	±0.35% Full Scale <i>Full Scale value = 35.42" Hg or 17.4 psia</i>	
Units	PSI, BAR, MBAR, KGCM2, MSW, FTSW, INHG, MMHG, KPA, MPA, TORR, INH2O@4°C, INH2O@20°C, INH2O@60°F, CMH2O@4°C, CMH2O@20°C, MMH2O@4°C, MMH2O@20°C, FTH2O@20°C, FTH2O@60°F, CUSTOM	
Power	3 AA Alkaline Batteries (LR6) Handheld, USB Power (Micro B) Panel Mount <i>1200+ Hours of typical use with low battery indication at 3.7 volts</i>	
Temperature	14°F to 122°F (-10°C to 50°C) <i>Compensated operating range</i>	-10°F to 150°F (-23°C to 65°C) <i>Storage (remove batteries over thirty days)</i>
Display	Tri-color graphics 240 x 120 – Real true type font with 0.6" digits	
Humidity	0 to 95% – Non-condensing	
Connection	¼" MNPT – 316 Stainless Steel	
Enclosure	Corrosion Resistant Aluminum – Powder Coated, IP65, 1.7 Pounds 4" Outer Diameter, 5.6" Height, 1.7" Depth	

All ETG series comply with Electromagnetic Radiated Emissions and Immunity per EN 61000-4-2:2008, EN 6100-4-3: 2000 and EN 61326-1:2013, and ETSI EN 301 489-1 V2.2.0 and RoHS Directive 2011/65/EU.



Part Number Configurator: Ordering Information

Model	Range	Sensor Type	Accuracy	Options
ETG = Handheld ETGP = Panel Mount	PSI Value	C = Compound I = Isolated	05 = 0.05% FS 10 = 0.1% FS 25 = 0.25% FS	BT = Bluetooth (Apple and Android)
Examples	ETG-15-C-05, ETG-30-C-05, ETG-15-I-05, ETG-30-I-05-BT, ETG-3K-I-10-BT, ETG-5K-I-25-BT ETGP-15-C-05, ETGP-30-C-05, ETGP-100-I-05, ETGP-300-I-05, ETG-1K-I-05, ETGP-3K-I-05, ETGP-5K-I-05, ETGP-10K-I-05			
Accessories				
WC00102 – 6ft USB to Micro B Cable (Right Angle)				
AS00100 – Data Management Software				
WC00101 – Spare AC Adapter to Micro B				

Phone: 888-797-3740 / Email: sales@vaetrix.com / 143 Raymond Rd, Candia, NH 03034 USA